

TFL FLEET TRACKING

More than just dots on a map.



Easy Operation

Plug the OBD-II GPS tracker onto your vehicles OBD-II port or simply hardwire the tracking unit using the optional 3-Wire Harness (P/N: TFL-5C848-8) to Power, Ground, and Ignition and start tracking immediately.



Reliable 4G LTE Network

TFL's fleet tracking devices communicate on America's most recognized 4G LTE nationwide network. This allows TFL to support your Fleet tracking needs for many more years to come.



Real-time Monitoring

Locate and monitor your fleet up to the second through our TFL Portal or mobile app.



Alerts & Reports

Receive real-time email and scheduled reports via email or portal/mobile app notifications. Create geofences and get alerts notifying you of vehicle movement at various points-of-interests.

Dimensions

1.8 x 2.6 x 1.1"
(46 x 67 x 28 mm)

Weight

1.75 oz (50 g)

Operating Temp.

-30C to +60C

Operating Voltage

9 to 32 VDC (start-up, operating)

Network

4G LTE Cat-1



Dimensions

3.7 x 2.0 x 0.8" (93.57mm
x 52.88mm x 19.68mm)

Weight

2.4 oz (68.03 g)

Operating Temp.

-30C to +75C

Operating Voltage

9 to 30 VDC (start-up, operating)

Network

4G LTE Cat-1

